

1. Drivers must wear long pants, long sleeved shirt, and closed toe shoes.
2. If you have an injury that requires you to wear a cast anywhere on your body, you will not be allowed to run.
3. Cars must have like engine like chassis.
4. Event will be stopped to pick up bumpers and axle shafts.
5. If bumper is missing, frame must be cut off.
6. No stiff suspensions; all cars must have original give and bounce.
7. Front and rear bumpers can only be looped one time. The chain must go through the hood and the trunk deck once on each side of the car.
8. Excessive body crimping is **NOT** allowed.
9. No welded motor mounts; however, they can be chained.
10. Two safety straps (1/8" x 2" solid steel strap bolted or welded one on each side) or bars securely attached from bottom of windshield is necessary. Must be evenly spaced to prevent hood from coming inside car. They must be bolted below hood line.
11. Cars that ran in last year's derby at the Chelsea Fair are allowed; all others must be fresh cars. No fresh car may be used for the final heat.
12. If there is a hole in the fire wall, it must be covered with sheet metal. No filling the hole with carpet or seat material the day of the derby.
13. No extra weights of any kind may be added.
14. Car tires only and air only. Remove all wheel weights.
15. Tires can not be screwed to rim; no studded tires.
16. Hood can be held down with a maximum of two chains that are no longer than 60 inches, chained in two spots—left front and right front.
17. No entries after 6:30 p.m. on the evening of the derby.
18. A hole must be in the hood, not to exceed 12".

19. Batteries must be moved to passenger compartment inside car.
20. All cars entered must have title at time of entry.
21. The winning driver of the Feature on Tuesday cannot run in any event on Wednesday.
22. Steel fuel line must be used instead of rubber fuel line through the firewall, with a minimum length of 36 inches.
23. High-pressure fuel hose **MUST** be used on all cars with fuel injection. Must have fuel injection hose, double clamped at both ends.
24. **A BOAT TYPE TANK** or equivalent must be placed in rear of car. The tank must be flat, no upright 5 gallon cans. Gas line or hose must be secure to nozzle of tank with hose clamp. Tank must be securely fastened to floor of car. A non-flammable fire wall is required over tank. Gas line must be run through fire wall on floor under seat. Original gas tank must be removed from car.
25. Original bumpers must remain on car.
26. Reinforcement of driver's door is **MANDATORY!** No cement, no I-beam, no guard rail.
27. The minimum reinforcement size is 3" wide, 3/8" thick and may not exceed 2" protruding from car. It **MUST** be bolted on each end with 3/8" or larger bolts and must extend 4" past door seams. **YOU MUST HAVE TWO BRACES EVENLY SPACED ON DRIVER'S DOOR!**
28. No anti-freeze.
29. Judge's discretion is FINAL!
30. Driver's social security number must be provided.